

## PORTABLE SOLAR POWERED COMPOUND CCTV.

# SITE & COMPOUND SECURITY

SOLAR POWERED SURVEILLANCE FOR YOUR SITE OR COMPOUND

Our latest innovation is the perfect partner for Site & Compound Security. This clever solar powered solution protects your compound with motion detection and alerts 24/7 with Night Vision technology.

The Invictus Hybrid CCTV camera requires no collaboration and can be tailored to:

- Detect Objects of Specific Sizes - Set your own minimum & maximum sizes.
- Detect Objects' Shapes - Users can choose to ignore wide objects (e.g. vehicles, but can detect tall objects (e.g. people)
- Set your region of interest - Only detect movement within certain parameters.

This clever camera continually learns the background of a scene including moving foliage and changes in lighting conditions, ensuring that only objects moving through the scene trigger an alert.



## KEY BENEFITS

- Exceptionally clear image even in low light conditions.
- Solar powered and portable.
- Monitor remotely using EdgeVis software.
- 24/7 support from our friendly team.

## TECHNICAL SPECIFICATIONS



## INVICTUS HYBRID

### Details

- INV-32U-IR
- Invictus ULTRA 32:1
- HYBRID 1080p
- ULTRA low Light
- HMA
- Wiper
- IR

### SOLAR IP

### Trailer

**Length** (overall): 3000mm  
**Width** (operating position): 1760mm  
**Height** (travel position): 2500mm  
**Height** (max operating position): 6600mm  
**Weight:** 690kg  
**Power Voltage:** 12v, 24v, 48v  
**Solar Panels:** 2x 250w panels  
**Operation:** Batteries / solar

## FEATURES

**Picture Flip & Freeze:** Yes  
**Focus/Iris:** Auto / Manual  
**Presets:** 101  
**Tours:** 4 (max 90 presets per tour)  
**Learned Patrols:** 4 mimic tours - up to 10 mins duration each  
**Privacy Zones:** Up to 24  
**Variable pan speed / coverage:** 0.1 - 120°/sec, 360° continuous rotation, absolute positioning  
**Variable tilt speed / coverage:** 0.1 - 120°/sec, 160°, absolute positioning  
**Auto Homing:** Goes to preset, tour or mimic tour after prescribed time  
**Col / Mono Changeover:** 4 levels - 3 fixed, 1 custom /user defined  
**Operating temperature:** -30°C to +60°C  
**Certification:** IP66

